

Solar Light(SS-06)



SS-06	DESCRIPTIONS
Solar Panel	Material: 15W Multicrystalline silicon (tempered glass encapsulated) Life time: 15 years
Battery Group	18 x 1.2V/6Ah Ni-MH batteries Life time: 5-8 years
Controller	a. Switch on automatically with light sensor b. Switch off automatically with built-in timer (default: 8 hours) c. Battery over-current and over-discharge protection
Pole	a. Cast aluminum pole and plastic-coated b. Stainless hexangular screw for connection
Light Source	a. Super bright white 9W LED lamp (360 lumens) b. Luminance equivalent to one 90W incandescent lamp c. Life time: 100,000hrs
Working Conditions	a. Continuous Working duration under cloudy weather: 3-5 days b. Lighting range: 15 meters; Height: 230cm c. Ambient temperature: -40 °C ~+ 80 °C
Packaging	a. Carton size: 90cm x40cm x50cm (1 unit per carton) b. Carton gross weight: 15kg ; Carton net weight: 13kg c. Carton volume: 0.18m <sup>3</sup> ; Carton volume weight: 30kg d. Q'ty/ 20'FCL: 155pcs; Q'ty/ 40' FCL: 316pcs
Features	High capacity Ni- MH battery group is adopted. Function well under low temperature. Elegant in design and safe for use –no wire and low voltage. Convenient for self-assembling and environment friendly.